

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 12 only, (East)T27-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4798-99) and (Dup. Pg. 9837, Vol. 23)

Set a basalt stone 15x10x6 ins., 10" in ground for cor. of secs. 1, 6, 7 and 12, marked with 1 notch on N. and 5 notches on S. edges, from which

- A Fir 10" dia., bears N.15°E., 16 lks. dist. mkd. T27S R1E S6 BT.
- A Fir 8" dia., bears S.85°E., 45 lks. dist. mkd. T27S R1E S7 BT.
- A Fir 30" dia., bears S.20°W., 30 lks. dist. mkd. T27S R1W S12 BT.
- A Fir 8" dia., bears N.89°W., 6 lks. dist. mkd. T27S R1W S1 BT.

GL0 resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9850)

Intersect the old cor. established for secs. 1, 6, 7 and 12, which is a basalt stone, 12x6x10 ins., above ground, mkd. with one notch on the N. and 5 notches on the S. edges.

I change this cor. to refer to secs. 1 and 12 only, destroying the scribe marks on the NE. and SE. bearing trees. Alongside of old cor. stone;

Set an Iron post 3 ft. long, 2" dia., 27" in the ground for the cor. of secs. 1 and 12 only, with brass cap marked:

T27S		T27S
S 1		S 7
S12		
R1W		R1E
1927		

from which

- A Fir 12" dia., bears N.15°E., 16 lks. dist. mkd. T27S R1E S6 BT. (Old BT)
- A Fir 12" dia., bears S.85°E., 45 lks. dist. mkd. T27S R1E S7 BT. (Old BT)
- A Fir 34" dia., bears S.20°W., 30 lks. dist. mkd. T27S R1W S12 BT. (Old BT)
- A Fir 10" dia., bears N.89°W., 6 lks. dist. mkd. T27S R1W S1 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 30, 1969 - C.S. File 54/94-25

Found - 1927 GL0 brass cap buried and marked incorrectly.
(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Not having any stamps, I remove marks referring to secs. 6 & 7.
RESET brass cap at sec. cor., now mkd. General Land Office
1927
Found - Original stone in place.
34" now 38" D.Fir S.20°W., 19.8 ft., shows good scar
6" now 10" Hemlock N.89°W., 4.0 ft. shows good scar.