

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9939-40)

-----  
At intersection (2.87 chs. N.0°04'W. of sec. cor. for 1 & 12), Set an Iron post 3 ft. long, 2" dia., 27" in the ground for the closing cor. of secs. 6 & 7, with brass cap marked:

T27S	T27S	
S 1	$\frac{S\ 6}{S\ 7}$	C C
R1W	R1E	
1928		

from which

A Fir 60" dia., bears N.10°E., 60 lks. dist. mkd. T27S R1E S6 CC BT.

A Hemlock 6" dia., bears S.75°E., 38 lks. dist. mkd. T27S R1E S7 CC BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 30, 1969 - C.S. File 54/94-25

-----  
Section corner found OK.