

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9851-52)

-----  
Point for the ¼ sec. cor. of sec. 6 only.  
Set an Iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 6 only, with brass cap marked:

    |¼ S 6  
    1927

from which

- A Fir 6" dia., bears N.53°E., 120 lks. dist. mkd. ¼ S6 BT
- A Fir 8" dia., bears N.84°E., 244 lks. dist. mkd. ¼ S6 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 30, 1969 - C.S. File 54/94-26

-----  
Found - 1927 GLO brass cap at ¼ cor., properly marked.  
6" now 20" D.Fir, N.53°E., 79.2 ft., shows scar.  
8" now 20" D.Fir, N.84°E., 161.0 ft., shows scar.  
New BTs- 13" D.Fir N.82½°E., 16.0 ft. mkd. ¼ S6 CS BT.  
14" D.Fir S.68°E., 23.7 ft. mkd. ¼ S6 CS BT.