

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 31 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9827 & Vol. 24 Page(s) 10241)

-----  
Set post 44x4" firmly in the ground for stand. ¼ sec. cor. marked S C on N & S faces from which  
A fir, 18" dia., bears N.10°E., 35 lks., mkd: S C ¼ S BT.  
A fir, 18" dia., bears S.2°W., 21 lks., mkd: S C ¼ S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitman, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10262)

-----  
The old Cor. established for standard ¼ cor. of sec. 31 (West 1.97 chains and North 27 lks. (from new corner))  
I destroy all evidence of this corner.  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for standard ¼ sec. cor., with brass cap marked  
SC  
¼ S 31  
1927  
from which  
A fir, 48" dia., bears N.65°E., 86 lks., mkd: ¼ S31 SC BT.  
A fir, 30" dia., bears N.56°W., 73 lks., mkd: ¼ S31 SC BT.  
(Page 10354 - 1/4 Cor. Sec. 6 only bears West 1.81 Chains)