

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9923)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 30}{S\ 31}$
1927

from which

- A fir, 14" dia., bears N.70°E., 40 lks., mkd: 1/4 S30 BT.
- A fir, 16" dia., bears S.15°E., 43 lks., mkd: 1/4 S31 BT.

Bruce A. Shaner - USFS - Dec. 1965 - C.S. File 51/332

- Found - U.S. GLO Brass Cap from which:
- 20" Fir Stump, (Orig. BT), now windthrown, bears N.70°E. 26.4 ft.
 - 22" Fir BT. Stump (orig. BT), now windthrown, bears S.15°E. 28.4 ft.
- Scribed- 40" D.Fir Stump, scribed S30 1/4 S BT, now bears N.38°W., 20.0 ft.
- 26" D.Fir Stump, scribed S31 1/4 S BT, now bears S.3°W. 24.1 ft.