

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9934-5)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S \ 7}{S \ 18}$
1927

from which

A fir, 16" dia., bears N.50°E., 34 lks., mkd: 1/4 S7 BT.

A hemlock, 10" dia., bears S.49½°E., 42 lks. mkd: 1/4 S18 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 23, 1969 - C.S. File 54/94-12

Found - 1927 GLO Brass Cap, properly marked.
16", now 18" D.Fir, N.50°E. 22.4 ft., shows good scar..

10", now 15" Hemlock S.49½°E., 27.7 ft., rotten face, scribe visible.

New BT - 18" D.Fir S.12°W. 21.0 ft. mkd: "1/4 S18 CS BT"

All other bearing trees tagged.

This corner lies about 30 ft. south of draw, course E-W.