

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 178100

PRIMARY CORNER DESCRIPTION Cor. Secs. 5 & 6 only; T28-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10351)

-----

1.81 chs. West from the standard cor. of secs. 31 & 32:T27-1E  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for closing cor. of secs. 5 & 6, with brass cap mkd

T27S R1E	
S 31	
S 6	S 5
T28S	R1E
C	C
1928	

from which

A hemlock, 14" dia., bears S.57 $\frac{3}{4}$ °E., 68 lks., mkd: T28S  
R1E S5 CC BT.

A hemlock, 12" dia., bears S.11 $\frac{1}{2}$ °W., 50 lks., mkd: T28S  
R1E S6 CC BT.