

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION South Cor. Secs. 31 & 32 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9827 & Vol. 24 Page(s) 10241-2)

Set post 48x4" firmly in the ground for stand. cor. to secs. 31 & 32 mkd S C T 27 S R 1 E on N S 32 E and S 31 on W faces with 5 notches on E and 1 on W edges, from which
A fir, 8" dia., bears N.25°E., 26 lks., mkd: T27S R1E S32 BT.
A fir, 9" dia., bears N.15°W., 37 lks., mkd: T27S R1E S31 BT.
A fir, 8" dia., bears S.45°W., 15 lks., mkd: S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10263)

The old cor. established for standard cor. of secs. 31 & 32, bears (West 2.2 chs and) N 45 lks. (From new Corner)
I destroy all evidence of this cor.
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for standard cor. of secs. 31 & 32, with brass cap mkd
S C
T27S | R1E
S 31 | S 32
T28S R1E
1927
from which
A hemlock, 10" dia., bears N.76½°E., 45 lks., mkd: T27S R1E S32 SC BT.
A fir, 24" dia., bears N.74°W., 48 lks., mkd: T27S R1E S31 SC BT.
(From pg 10351) 1.81 chs. East from the standard cor. of secs. 5 & 6; T28-1E