

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9921)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 29, 30, 31, & 32, with brass cap mkd

T27S R1E  
S 30|S 29  
S 31|S 32  
1927

from which

- A hemlock, 24" dia., bears N.62½°E., 46 lks., mkd: T27S R1E S29 BT.
- A hemlock, 24" dia., bears S.63°E., 62 lks., mkd: T27S R1E S32 BT.
- A hemlock, 24" dia., bears S.81°W., 6 lks., mkd: T27S R1E S31 BT.
- A hemlock, 14" dia., bears N.64°W., 22 lks., mkd: T37S R1E S30 BT.