

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9925)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T27S R1E  
S 19 | S 20  
S 30 | S 29  
1927

from which

- A fir, 34" dia., bears N.20°E., 53 lks., mkd: T27S R1E S20  
BT.
- A fir, 10" dia., bears S.26°E., 18 lks., mkd: T27S R1E S29  
BT.
- A fir, 48" dia., bears S.43°W., 44 lks., mkd: T27S R1E S30  
BT.
- A fir, 8" dia., bears N.8°W., 23 lks., mkd: T27S R1E S19  
BT.