

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9940-1)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 6 | S 5
1928

from which

A fir, 50" dia., bears N.30°E., 40 lks., mkd: 1/4 S5 BT.

A hemlock, 9" dia., bears S.71°W., 9 lks., mkd: 1/4 S6 BT.

Douglas Co. Surveyors Office - M. Lenora Lading - A. Vic Cangie - K. Cheney - Aug. 4, 1976 - C.S. 59/18-14

Found - 1928 GLO brass cap properly mkd. laying out of ground.

A 50" now 52" Fir stump N.30°E., 26.4 ft. with visible scribe in partly healed blaze.

A 9" now 16" Hemlock, S.71°W., 5.9 ft. Tree is alive with well healed blaze.

Reset - At true corner point: The USGLO Brass cap stamped "DCSO" 1976 above the 1928.

New BT - A 8" Hemlock bears N.40°E., 27.0 ft. scribed "1/4 S5 CS BT" in double blaze.