

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION S 1/4 Cor. Sec. 32 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9827-8 & Vol. 24 Page(s) 10242)

Set post 44x4" firmly in the ground for stand. ¼ sec. cor. marked S C on N & S faces from which
A pine, 30" dia., bears N.20°W., 38 lks., mkd: S C ¼ S BT.
A fir, 36" dia., bears S.20°W., 53 lks., mkd: S C ¼ S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10263-4)

The old Cor. established for standard ¼ cor. of sec. 32 (West 1.83 chains and S.53¼°W., 212 lks. (from new corner))
I destroy all evidence of this corner.
Set an iron post, 3 ft. long, 1" dia., 6" in the ground to bed rock, in a mound of stone, 5 ft. base, 2 ft. high, for standard ¼ sec. cor., with brass cap marked

SC
¼ S 32
1927

from which
A fir, 30" dia., bears N.37°E., 101 lks. mkd: ¼ S32 SC BT.
A fir, 14" dia., bears N.61°W., 49 lks., mkd: ¼ S32 SC BT.
From N¼ S5 T28-1E, bears East 1.80 chs