

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9926)

-----

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 20  
S 29  
1927

from which

A fir, 42" dia., bears N.42°E., 71 lks., mkd: 1/4 S20 BT.

A hemlock, 26" dia., bears S.14°W., 42 lks., mkd: 1/4 S29 BT

Douglas Co. Surveyors Office - Randy Smith & Ed Monrean, Deputies - 6/19/2000 - C.S. File 66/16-15

-----

Found - USGLO monument 2 1/2" dia., brass cap on a 1" dia., gal. pipe, bent 18" above ground, mkd: "1/4 S20/S27 1927"  
26" Hemlock now 30" stump 5' high, scribed "1/4 S29" visible in blaze, bears S.11°W. (rec. S.14°W.)  
27 ft. rec. 27.7.

Not Fd - Bearing & dist. for NE BT falls in cat road.

New - 5" Fir, double blazed & scribed "1/4 S20 CS BT" bears N.42°W., 43.2 ft.

5" Fir double blazed & scribed "1/4 S29 CS BT" bears S.34°W., 48.7 ft.

8" spike in 48" dia., Fir stump 2 1/2 ft. high bears S.73°E., 29.1 ft. Set through DCSO BT tag.