

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION CC Secs. 32 & 33 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9828 & Vol. 24 Page(s) 10242)

Set post 48x4" firmly in the ground for stand. cor. to secs. 32 & 33, marked S C T 27 S R 1 E on N S 33 on E and S 31 on W faces with 4 notches on E and 2 on W edges from which
A fir, 18" dia., bears N.20°E., 33 lks., mkd: T27S R1E S33 BT.
A fir, 24" dia., bears N.23°W., 69 lks., mkd: T27S R1E S32 BT.
A fir, 18" dia., bears S.20°E., 73 lks., mkd: S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10264-5)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for standard cor. of secs. 32 & 33, with brass cap mkd
S C
T27S | R1E
S 32 | S 33
T28S R1E
1927
from which
A cedar, 14" dia., bears N.58°E., 65 lks., mkd: T27S R1E S33 SC BT.
A fir, 16" dia., bears N.60½°W., 113 lks., mkd: T27S R1E S32 SC BT.
(East, 1.79 chs from the cor. of Secs. 4 & 5)