

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9907)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 32 | S 33
1927

from which

- A fir, 24" dia., bears N.70°E., 35 lks., mkd: 1/4 S33 BT.
- A fir, 24" dia., bears N.75°W., 48 lks., mkd: 1/4 S32 BT.

Dennis Gaylord, USFS & Deputy, Doug. Co. Surveyors Office -
Witness: Darrel Myers - Aug. 14, 1979 - C.S. File 60/34-10

-
- Found - 1927 USGLO brass cap marked USGLO 1/4 S32 S33 1927.
A 32" W.Fir snag bears N.75°W., 31.68 ft. scribing visible on a nearly healed and rotted blaze.
A 28" W.Fir bears N.75°E., 23.1 ft. (Rec. in N.70°E.)

- Set - I add "T27S R1E" to brass cap
New BTs- A 6" W.Fir bears N.83°W., 34.6 ft. scribed "1/4 S32 CS BT" on double blazes.
A 5/8" I.Rod with a 1 1/2" Alum, cap, marked "RM" bears S.8°E., 21.2 ft.
A 5/8" I.Rod with a 1 1/2" Al. cap marked "RM" bears N.26°W., 36.5 ft.

Corner is located in a salvage logging unit which will be logged this fall.