

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9910)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd

T27S R1E
S 20 | S 21
S 29 | S 28
1927

from which

- A fir, 28" dia., bears N.78°E., 52 lks., mkd: T27S R1E S21
BT.
- A fir, 14" dia., bears S.28°E., 62 lks., mkd: T27S R1E S28
BT.
- A fir, 14" dia., bears S.78°W., 51 lks., mkd: T27S R1E S29
BT.
- A fir, 20" dia., bears N.12°W., 94 lks., mkd: T27S R1E S20
BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Gary Commins - John Campbell, USFS - July 21, 1972 - C.S. File 54/94-115

Found - 1927 GL0 Brass cap in place & stumps of 3 original BTs. Cut too low for scribe. This corner is in clear cut unit. No trees close for BTs.

Set - 6' Steel fence post alongside corner monument.
5/8" Iron rod S.32°E., 6.7 ft. on west side of 30" Fir stump.
5/8" Iron rod S.48°W., 9.8 ft. on north side of 32" Fir stump.

Note - This corner lies on moderate N. slope approx. 400' N. of log landing.