

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION WC Secs. 16, 17, 20, & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9912)

-----

(WC)  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for Witness cor. of secs. 16, 17, 20, & 21, with brass cap mkd  
W C  
T27S R1E  
S 17|S 16  
S 20|S 21  
1927

from which  
A cedar, 8" dia., bears N.73°E., 36 lks., mkd: W C T27S R1E S21 BT.  
A fir, 10" dia., bears S.34°E., 45 lks., mkd: W C T27S R1E S21 BT.  
A fir, 14" dia., bears S.34°W., 53 lks., mkd: W C T27S R1E S20 BT.  
A fir, 26" dia., bears N.30°W., 18 lks., mkd: W C T27S R1E S20 BT.  
N.0°03'W., 0.55 chs.  
True point for cor. falls in the East fork of Hemlock Creek, 7 lks wide, course W., where it is impracticable to establish sec. cor.