

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9915)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T27S R1E  
S 8 | S 9  
S 17 | S 16  
1927

from which

- A fir, 18" dia., bears N.56°E., 60 lks., mkd: T27S R1E S9 BT.
- A fir, 22" dia., bears S.57½°E., 35 lks., mkd: T27S R1E S16 BT.
- A fir, 24" dia., bears S.33°W., 36 lks., mkd: T27S R1E S17 BT.
- A fir, 22" dia., bears N.49°W., 63 lks., mkd: T27S R1E S8 BT.