

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 32, & 33 T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9865-6)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 32, & 33, with brass cap mkd

T26S R1E  
S 32 | S 33  
S 5 | S 4  
T27S  
1927

from which

- A hemlock, 14" dia., bears N.8°E., 46 lks., mkd: T26S R1E S33 BT.
- A fir, 12" dia., bears S.23°E., 57 lks., mkd: T27S R1E S4 BT.
- A hemlock, 5" dia., bears S.57°W., 40 lks., mkd: T27S R1E S5 BT.
- A fir, 30" dia., bears N.54°W., 45 lks., mkd: T26S R1E S32 BT.