

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9910-1)

A fir, 30" in dia., for the 1/4 sec. cor. I mark

1/4 S 21 on the N and
S 28 on the S sides.

from which

A pine, 14" dia., bears S.26°W., 22 lks., mkd: 1/4 S28 BT.

A pine, 14" dia., bears N.40°W., 42 lks., mkd: 1/4 S21 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Gary Commins - John Campbell, USFS - July 21, 1972 - C.S. File 54/94-114

Found - Original 30" Corner tree, now 34" in diam. Scars on N. & S. sides Alive and in good condition.

Set - 5/8" Iron rod on NE side at base 2.0 ft. from center of tree.

Found - 14", now 16" dead pine, N.40°W., 14.5 ft. Recorded to be 27.7 ft. Scribe visible on unhealed blaze.

14", now 16" dead pine, S.26°W., 27.7 ft., Recorded to be 14.5 ft. Scribe visible on unhealed blaze.

Apparently the distances were turned around.

New BTs- 9" Hemlock, N.26 1/2°W., 11.2 ft. scribed "1/4 S21 CS BT"

6" Hemlock, S.74°E., 7.5 ft. scribed "1/4 S28 CS BT".

Note - Bearings & distances is from original corner tree.