

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION CC Secs. 33 & 34 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9829 & Vol. 24 Page(s) 10243)

-----  
Set post 48x4" firmly in the ground for stand. cor. to secs. 33 & 34, marked S C T 27 S R 1 E on N S 34 on E and S 33 on W faces with 3 notches on E & W edges, from which

A pine, 36" dia., bears N.40°E., 18 lks., mkd: T27S R1E S34 BT.

A pine, 48" dia., bears N.30°W., 27 lks., mkd: T27S R1E S33 BT.

A pine, 30" dia., bears S.1°E., 25 lks., mkd: S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10266)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for standard cor. of secs. 33 & 34, with brass cap mkd

S C  
T27S | R1E  
S 33 | S 34  
1927

from which

A hemlock, 22" dia., bears N.52½°E., 37 lks., mkd: T27S R1E S34 SC BT.

A fir, 20" dia., bears N.69½°W., 27 lks., mkd: T27S R1E S33 SC BT.

(175 lks East from the standard cor. of Secs. 3 & 4)