

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9897)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 21, 22, 27, & 28, with brass cap mkd

T27S R1E  
S 21|S 22  
S 28|S 27  
1927

from which

- A hemlock, 12" dia., bears N.57½°E., 38 lks., mkd: T27S R1E S22 BT.
- A hemlock, 48" dia., bears S.45°E., 48 lks., mkd: T27S R1E S27 BT.
- A fir, 48" dia., bears S.45½°W., 35 lks., mkd: T27S R1E S28 BT.
- A hemlock, 16" dia., bears N.44°W., 54 lks., mkd: T27S R1E S21 BT.