

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION CC Secs. 34 & 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9829-30 & Vol. 24 Page(s) 10244)

Set post 48x4" firmly in the ground for stand. cor. to secs. 34 & 35 marked S C T 27 S R 1 E on N sec. 35 on E and S 34 on W faces with 2 notches on E and 4 on W edges from which,
A fir, 14" dia. bears N.25°E., 6 lks. mkd: T27S R1E S35 BT
A fir, 8" dia. bears N.15°W., 12 lks. mkd: T27S R1E S34 BT
A fir, 30" dia., bears S.35°W., 19 lks., mkd: S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 10267-8)

The old cor. established for standard cor. of secs. 34 & 35, bears (West 6.81 chs.) & S.7¾°E., 122 lks. of CC Secs 34 & 35 I destroy all evidence of this cor.
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for standard cor. of secs. 34 & 35, with brass cap mkd
S C
T27S | R1E
S 34 | S 35
T28S | R1E
1927

from which
A fir, 20" dia., bears N.52°E., 19 lks., mkd: T27S R1E S35 SC BT.
A fir, 24" dia., bears N.60°W., 13 lks., mkd: T27S R1E S34 SC BT.