

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9882-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd

T27S R1E  
S 27|S 26  
S 34|S 35  
1927

from which

- A fir, 26" dia., bears N.46°E., 28 lks., mkd: T27S R1E S26  
BT.
- A fir, 30" dia., bears S.44°E., 31 lks., mkd: T27S R1E S35  
BT.
- A fir, 30" dia., bears S.30°W., 63 lks., mkd: T27S R1E S34  
BT.
- A fir, 20" dia., bears N.37°W., 51 lks., mkd: T27S R1E S27  
BT.