

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9891-2)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 10, & 11, with brass cap mkd

T27S R1E  
S 3 | S 2  
S 10 | S 11  
1927

from which

- A fir, 40" dia., bears N.25°E., 52 lks., mkd: T27S R1E S2  
BT.
- A fir, 40" dia., bears S.9°E., 37 lks., mkd: T27S R1E S11  
BT.
- A fir, 30" dia., bears S.58°W., 45 lks., mkd: T27S R1E S10  
BT.
- A fir, 48" dia., bears N.25°W., 75 lks., mkd: T27S R1E S3  
BT.