

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 34, 35; 2, & 3; T26-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9863)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd

T26S R1E  
S 34 | S 35  
S 3 | S 2  
T27S  
1927

from which

- A fir, 30" dia., bears N.48°E., 34 lks., mkd: T26S R1E S35 BT.
- A fir, 18" dia., bears S.50°E., 65 lks., mkd: T27S R1E S2 BT.
- A fir, 24" dia., bears S.60°W., 65 lks., mkd: T27S R1E S3 BT.
- A chinquapin, 7" dia., bears N.15°W., 45 lks., mkd: T26S R1E S34 BT.