

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 35 only;

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9830 & Vol. 24 Page(s) 10244)

-----

Set post 44x4" firmly in the ground for stand. ¼ sec. cor. marked S C on N & S faces from which

    A pine, 14" dia., bears S.65°W., 27 lks., mkd: S C ¼ S BT.

    A pine, 12" dia., bears N.43°E., 30 lks., mkd: S C ¼ S BT.

Peak of Quartz Mountain S.25°E., say 20 chains dist.

---

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 1068)

-----

The old cor. established for standard ¼ cor. of sec. 35, bears (West 6.47 chs and) S.2½°E., 126 lks.

I destroy all evidence of this cor.

335 ft. below spur

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for standard ¼ sec. cor., with brass cap marked

SC  
¼ S 35  
1927

from which

    A fir, 24" dia., bears N.81°E., 95 lks., mkd: ¼ S35 SC BT.

    A pine, 12" dia., bears N.85°W., 53 lks., mkd: ¼ S35 SC BT (1/4 cor. sec. 2 bears West 1.57 chs.)