

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. T27-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Samuel C. Flint, Deputy Surveyor, under Contract No. 473, dated June 5, 1883 - (DCSO Records Vol. 23 Page(s) 9831 & Vol. 24 Page(s) 10245-6)

Set post 48x4" firmly in the ground for stand. cor. to Tps. 27 S R1 & R2 E marked S C T27S on N R2E S31 on E and R1E S36 on W faces with 6 notches on N E & W edges, from which
A fir, 30" dia. bears N.70°E., 28 lks mkd: T27S R2E S31 BT
A fir, 12" dia. bears N.43°W., 55 lks mkd: T27S R1E S36 BT
A pine, 36" dia., bears South, 10 lks., mkd: S BT.

GLO resurvey by Lincoln E. Wilkes, US Cadastral Engineer, Otto L. Draper & Norman D. Price, US Transitmen, under Special Instr. dated Dec. 21, 1920 - (DCSO records Vol. 24 Page(s) 1070)

The old cor. established for standard cor. of Tps. 27 S, Rs. 1 & 2 E, bears (West 8.56 chs and) S.14³/₄°W., 94 lks.
I destroy all evidence of this cor.
Set an iron post 3 ft. long, 3" dia., 28" in the ground, for standard cor. of T27S Rs 1 & 2 E, with brass cap mkd.

SC
T27S
R1E | R2E
S 36 | S 31
T28S R2E
1927

from which
A fir, 16" dia., bears N.64°E., 15 lks., mkd: T27S R2E S31 SC BT.
A fir, 36" dia., bears N.68°W., 56 lks., mkd: T27S R1E S36 SC BT.