

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Cor. Secs. 24, 25; 19, & 30 T27-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9855-6)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 24, 25, & 30, with brass cap mkd

T27S  
R1E | R2E  
S 24 | S 19  
S 25 | S 30  
1927

from which

- A fir, 34" dia., bears N.35°E., 59 lks., mkd: T27S R2E S19 BT.
- A fir, 14" dia., bears S.17°E., 13 lks., mkd: T27S R2E S30 BT.
- A fir, 16" dia., bears S.70°W., 22 lks., mkd: T27S R1E S25 BT.
- A fir, 34" dia., bears N.18°W., 155 lks., mkd: T27S R1E S24 BT.