

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 24; 18 & 29 T27-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9857)

-----

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 18, 19, & 24, with brass cap mkd

T27S	
R1E	R2E
S 13	S 18
S 24	S 19
1927	

from which

- A fir, 26" dia., bears N.49°E., 80 lks., mkd: T27S R2E S18 BT.
- A fir, 12" dia., bears S.74°E., 27 lks., mkd: T27S R2E S19 BT.
- A fir, 8" dia., bears S.11½°W., 13 lks., mkd: T27S R1E S24 BT.
- A fir, 22" dia., bears N.52½°W., 49 lks., mkd: T27S R1E S13 BT.