

TOWNSHIP 27 RANGE 01E POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Cor. Secs. 12, 13, 7 & 18 T27-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9858)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T27S	
R1E	R2E
S 12	S 7
S 13	S 18
1927	

from which

- A fir, 30" dia., bears N.46°E., 9 lks., mkd: T27S R2E S7 BT.
- A hemlock, 12" dia., bears S.18°E., 48 lks., mkd: T27S R2E S18 BT.
- A fir, 36" dia., bears S.52°W., 13 lks., mkd: T27S R1E S13 BT.
- A fir, 8" dia., bears N.59°W., 17 lks., mkd: T27S R1E S12 BT.