

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Stand. cor. S. 31, T27-1; & S. 36, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4867-68)

Set Fir post 4 ft. long, 4" sq., 24" in the ground for
standard corner to T27S Ranges 1 and 2 W., marked S C T27S on
N.; R1W S31 on E.; and R2W S36 on W. with 6 notches on N.,
E., and W. faces, from which

A Fir 12" dia., bears N.10°E., 41 lks. dist. mkd. T27S R1W
S31 BT.

A Fir 24" dia., bears N.55°W., 16 lks. dist. mkd. T27S R2W
S36 BT.

A Fir 30" dia., bears S.35°W., 30 lks. dist. mkd. T28S R2W
S1 BT.

This township corner is located on S. side of a rocky
mountain 4000 ft. high.

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4780)

I destroy the old stand cor. and reestablish it at the point
of intersection of the random line with the 6th stan. par. S.
as follows:

Set a basalt stone 15x12x10 ins., 10" in the ground for stand
cor. of Tps. 27 S., Rs. 1 and 2 W., marked S C on N. and with
6 grooves on N., E., and W. faces, and raised a mound of
stone, 2 ft. base, 1½ ft. high, N. of cor. Pits
impracticable, from which

A Fir 16" dia., bears N.71°W., 62 lks. dist. mkd. T27S R2W
S36 BT.

No other trees in limits.

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4902)

Remains of old Tp. cor. set in 1881, contract #392, post
found destroyed, but bearing trees which are marked on the
bark, were in good condition. I entirely destroy all marks
on same.

GLO survey by Fred Mensch, U.S. Cadastral Engineer, under
Special Instructions, dated June 7, 1922 - (DCSO records Vol.
12 Page(s) 4961-62)

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Stand. cor. S. 31, T27-1; & S. 36, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The standard cor., which is a basalt stone, 12x10x5 ins., above ground, firmly set, mkd. SC on N., with 6 grooves on N., E., and W. faces, from which

A Fir 16" dia., bears N.71°W., 62 lks. dist. mkd. T27S R2W S36 SC BT. (Old BT)

No tree available for bearing tree, in sec. 31; raise a mound of stone 3 ft. base, 1½ ft. high N. of cor.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Sept/Oct. 1968 - C.S. File 54/40

Found - No trace of Corner stone or mound of stone called for.

Found - Orig. 16" now 38" Fir, N.71°W., 40.9 ft., shows faint scar. We open and find scribe marks.

Set Brass cap at cor. mkd: County Surveyors Office
T27S R2W S 36 S 31 R1W
T28S 1968

New BTs- 16" D.Fir N.61°E., 34.0 ft. mkd. T27S R1W S31 SC CS BT.

Orig. 38" R.Fir N.71°W., 40.9 ft. mkd. T27S R2W S36 SC CS BT.

This corner lies on very steep, southerly slope about 300 ft. S. of high rock bluff. The C C of T28S R's 1 & 2, bears West 413 ft.