

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100178

PRIMARY CORNER DESCRIPTION C C for Secs. 25 & 36 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4919)

At point of intersection, I set a Cedar post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 25 and 36 marked CC T27S R2W on W.; S25 on N. and S36 on S. face, with 1 groove on S. and 5 grooves on N. faces, from which
A Hemlock 18" dia., bears S.76°30'W., 51 lks. dist. mkd. T27S R2W S36 BT.
A Hemlock 12" dia., bears N.76°W., 38 lks. dist. mkd. T27S R2W S25 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - M. Stone, crew - Sept. 1962 - C.S. File 49/28-6

Found - Old Cedar stake some scribing still visible "S25". Hemlock, broken off and dead, S.76½°W., 33.7 ft. Perfect scribing still visible on open face "T27S R2W S36 B."
Hemlock now 12", N.76°W., 25.1 ft. scribing visible "T27S R2W".

Set Brass cap at cor. mkd: County Surveyors Office
T27S R2W S 25 | R1W CC
S 36 |
1962

Set orig. post alongside and erect rock mound.
New BTs- 20" Hemlock S.22°W., 42.3 ft. mkd. T27S R2W CC S36 CS BT.
19" R.Cedar N.64°W., 23.0 ft. mkd. T27S R2W CC S25 CS BT.
Corner falls in White Creek near East bank.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1968 - C.S. File 54/40-104

Found - No trace of 1962 DCSO brass cap due to 1964 flood. Orig. 12" Hemlock, alive, N.76°W., 25.1 ft., scribe visible.
Orig. SW. BT, gone, due to logging.
20" Hemlock, alive and OK, S.22°W., 42.3 ft.
19" R.Cedar, alive and OK, N.64°W., 23.0 ft.

We measure 25 ft. W. from true corner and at point set Witness Corner.

Set Brass cap at cor. mkd: County Surveyors Office
T27S R2W S 25 | CC R1W
S 36 |
1968

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100178

PRIMARY CORNER DESCRIPTION C C for Secs. 25 & 36 only, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Rescribed BTs:

20" Hemlock S.12°E., 40.0 ft. mkd. W.C. T27S R2W S36
CC CS BT.

19" R.Cedar N.23°E., 12.0 ft. mkd. W.C. T27S R2W S25
CC CS BT.

True corner falls in center of creek, 25 ft. E. of Wit. Cor.
This corner bears S.19°W., 99.4 ft. from W.C. secs. 30 & 31,
T27-1W.

Gerald V. Nygren, LS 1035 - Oct. 1988 - C.S. File 63/69-32

Found - A 1½" Iron pipe with brass extending 14" above
ground.

An 18" Cedar bears N.23°E., 12.0 ft., visible
scribing.

A 20" Hemlock, dead and down, bears S.12°E., 40.0 ft

New BT - 5 ft. D.Fir bears S.14°E., 30.7 ft. scribed "WC" on
small upper blaze and "BT" on small lower blaze.

Set 1/2" brass washer in BT face mkd. "LS 1035".

Bearing tree and monument signs were placed on all BTs
without them and a 6" red band and face blazes were painted
on all bearing trees.