

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4873)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼
sec. cor. mkd. ¼ S on E. and W. faces, from which
A Cedar 7" dia., bears S.75°W., 12 lks. dist., mkd. ¼ S BT
A Cedar 36" dia., bears S.40°E., 30 lks. dist., mkd. ¼ S
BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4781-82)

Set basalt stone 16x10x5 ins., 11" in the ground for ¼ sec.
cor., mkd. ¼ on W. face, from which
A Cedar 18" dia., bears N.16°E., 46 lks. dist. mkd. ¼ S30
BT.
A Cedar 20" dia., bears N.41°W., 36 lks. dist. mkd. ¼ S25
BT.
From this cor. the old ¼ sec. cor. bears N.87½°W., 2.20 chs.
dist. I destroy the old cor.

GLO survey by Morris Wygant, compassman for Zachariah M.
Derrick, U.S. Deputy Surveyor, under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4908)

The ¼ sec. cor. which is a stone, firmly set, mkd. and
witnessed as described by the surveyor general and which I
now change to refer to sec. 30 T27S R1W only.

Survey by Ronald A. Quimby - For: U.S. Forest Service - May
1980 - M 83-78

Set 2½" Iron pipe with brass cap mkd. "T27S R1W S30 only RLS
1654 1980.", from which
6" Cedar bears S.64°W., 15.8 ft. scribed "¼ S30 BT".
7" Hemlock bears N.9°W., 17.8 ft. scribed "¼ S30 BT"
16" Hemlock bears S.44°E., 19.9 ft. scribed "¼ S30 BT"
Brass washers mkd. RLS #1654 set in BT faces. Also set post
and sign 4.5 ft. North.

Gerald V. Nygren, LS 1035 - Oct. 1988 - C.S. File 63/69-31

Found - 2½" Iron pipe with brass cap.
An 8" Cedar bears S.64°W., 15.8 ft., visible
scribing. (Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An 8" Hemlock bears N.9°W., 17.8 ft., visible scribing.
A 16" Hemlock stump bears S.44°E., 19.9 ft. visible scribing.
New BT - A 7" Cedar bears S.25°E., 14.9 ft. scribed "¼ S30 BT". Set ½" brass washer in BT face mkd. "LS 1035".