

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100279

PRIMARY CORNER DESCRIPTION C C for secs. 24 & 25 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4921)

At point of intersection (92 lks. S.0°45'E. of cor. of secs. 19 & 30), I set a Fir post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 24 & 25 marked CC T27S R2W on W.; S24 on N. and S25 on S. face with 2 grooves on S. and 4 grooves on N. face, from which
A Fir 18" dia., bears S.6°15'W., 119 lks. dist. mkd. T27S R2W S25 BT.
A Fir 36" dia., bears N.12°40'W., 80 lks. dist. mkd. T27S R2W S24 BT.

Douglas Co. Surveyors Office - L.E. Monrean and P.L.Earle - May 21, 1975 - C.S. File 57/30-1

Found 42" Fir snag scribed "T27S R2W S24 BT". Other BT not found, Corner post not found.
Set Brass cap at closing corner, stamped:
County Surveyors Office

			T 27 S		
R	C	S 24		S30	R
2	C	S 25			1
W		1975			W

New BTs- 17" Hemlock bears S.51°W., 40.2 ft. scribed CC S25 T27S R2W CS BT.
16" Hemlock bears N.63°W., 26.0 ft. scribed CC S24 T27S R2W CS BT.
A stone 16"x10"x8" with 4 notches on one edge and 2 notches on the opposite edge, lying on surface of ground, bears N.4°W., 58.9 ft. (Rec. N.0°45'W., 60.7 ft.)