

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4872)

Set Maple post 3 ft. long, 3" sq., 24" in the ground for ¼
sec. cor. marked on E. and W. faces "¼ S" from which
A Fir 36" dia., bears S.30°E., 61 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears S.40°W., 38 lks. dist. mkd. ¼ S BT

GLO survey by Homer D. Angell, Deputy Surveyor, under
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11
Page(s) 4782-83)

Set basalt stone 15x8x6 ins., 10" in the ground for ¼ sec.
cor. marked ¼ on W. face, from which
A Fir 14" dia., bears S.40°E., 37 lks. dist. mkd. ¼ S19 BT
A Fir 36" dia., bears N.10°W., 16 lks. dist. mkd. ¼ S24 BT
From this corner, the old ¼ sec. cor. bears N.44°40'W., 2.47
chs. dist. I destroy the old cor.

GLO survey by Morris Wygant, compassman for Zachariah M.
Derrick, U.S. Deputy Surveyor, under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4909)

The ¼ sec cor which is a stone, firmly set, mkd & witnessed
as described by the surveyor general, and which I now change
to refer to sec. 19, T27S R1W only, bears West 5 lks. dist.

FD 2 BTs 4/1975 - DCSO L. Monrean - C.S. File 57/21-8

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - Karen
Cheney, crew - Feb. 23, 1977 - C.S. File 59/29-31

Found - 34" Fir (Rec. 36") bears N.10°W., 10.6 ft. Blaze
opened, old scribing visible "¼ S24 BT"
A 14" now 28" Fir bears S.37°E., 24.4 ft. (Rec.
S.40°E.) No scribing found, blaze is chopped out
Set 1" x 36" I.P. with brass cap attached at ¼ corner as
determined in found trees. Cap is stamped: "Douglas County
Surveyor T27S R1W 1/4 S19 1977."
I reblaze old bearing tree:
28" Fir bears S.37°E., 24.4 ft. scribed "¼ S19 CS
BT" on a single blaze.
Cor. lies on N-S cutting line. Timber is on East as the BT to
the NW. is the only evidence remaining of the 1902 and 1911
surveys. I do not remove the scribing referring to sec. 24,
although the 1911 notes indicate this is not ¼ for 24.

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Survey by Loyd R. Moffit, LS #944 - For: U.S. Forest Service
June 1986 - C.S. File 62/30-26

Found - 1977 DCSO 2" brass cap on a 1" iron pipe in a rock mound.

40" Fir stump bears S.38°E., 24.4 ft. scribe visible.

38" Fir stump bears N.10°W., 10.6 ft., scribe visible.

New BTs- I marked a 4" Fir which bears S.64°E., 7.7 ft. scribed "X BT".

I marked a 6" Fir which bears S.23°E., 36.7 ft. scribed "¼ S19 BT."

I nailed a L.S. 944 brass washer to both BT scribes.