

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100437

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only, T27-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Romano E. Ware - For: U.S. Forest Service - May 1977 - M 65-20

-----  
Set 2½" Iron pipe with brass cap in rock mound, stamped: "T27S R2W 1/4 S13| R1W 1977 LS 1005", from which new BTs:  
6" W.Fir bears N.61°W., 7.7 ft. scribed ¼ S13 BT.  
6" W.Fir bears S.29°W., 45.1 ft. scribed ¼ S13 BT.

John Ransom, USFS - Jonathan Drew - 2010 - C.S. File 65/72-21

-----  
Found - 3" Brass Cap on 2½" Galv Iron Pipe, Flush with mound of stone. Cap Marked "T27S ¼ R2W S13 R1W 1977 LS1005" For Section 13 ONLY  
17" Cedar N.61°W., 7.7 ft healed double blaze  
8" Fir S.29°W., 45.1 ft 15' tall snag, healed double blaze.

New - Painted 6" Band around BTs and painted face blazes, new nails on signs, cleared brush around corner, marked new tree  
16" Fir bears S.58°W., 26.43 ft scribed "¼ S13"BT" on double blaze

Remarks- Found steel post 2.8 ft. South, PB + LSM  
Drove Aluminum Post 2.3 ft North, Property Boundary and Land Survey Monument Signs attached.

Note - Corner falls on fairly level ground approx .4 miles north of road intersection. Take Forest Road 27 to Forest Road 2792 to the 040 Spur. Follow Spur to intersection with 020 Spur and 066 spur. Follow posted blazed line along PVT Clearcut North .4 miles to corner

PLANE COORDINATE POSITION DATA  
State OR Zone UTM-10M  
North 4785189  
East 510381  
Estab. By GCDB