

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 12 Page(s) 4871)

-----  
Set Maple post 3 ft. long, 3" sq., 24" in the ground for ¼  
sec. cor. marked ¼ S. on E. & W. faces, from which  
A Fir 60" dia., bears N.60°W., 50 lks. dist. mkd. ¼ S BT.  
A Fir 36" dia., bears S.60°E., 43 lks. dist. mkd. ¼ S BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4783)

-----  
Set basalt stone 15x10x8 ins., 10" in the ground for ¼ sec.  
cor. marked ¼ on W. face, from which  
A Fir 7" dia., bears S.18°E., 17 lks. dist. mkd. ¼ S18 BT  
A Fir 12" dia., bears S.55°W., 48 lks. dist. mkd. ¼ S13 BT  
After diligent search no old ¼ sec. cor. can be found.

GLO survey by Morris Wygant, compassman for Zachariah M.  
Derrick, U.S. Deputy Surveyor, under Contract #779, dated  
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4910)

-----  
Intersect the ¼ sec. cor. on W. bdy. sec. 18 which is a  
stone, firmly set, marked and witnessed as described by the  
surveyor general and which I now change to refer to sec. 18,  
T27S R1W only.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
June 20, 1969 - C.S. File 54/40-176

-----  
Found - Unrecorded U.S. Plywood Alum. cap mkd. ¼|S 18 only  
1962.  
Orig. 7" now 9" Hemlock S.18°E., 11.2 ft., lying  
face down, we roll over and find "¼ S18 BT"  
scribe under 40+ years of overgrowth. (Old field  
notes call for Fir)  
No trace of other BT.  
Corner stone called for is broken and small piece is  
mkd. "¼".  
New BTs- 54" D.Fir stump, N.69°E., 29.5 ft. mkd. ¼ S18 CS BT.  
50" D.Fir stump, S.22°E., 37.0 ft. mkd. ¼ S18 CS BT.  
Corner lies on N. slope in old clear cut area.

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Survey by Romanso E. Ware, LS #1005 - For: U.S. Forest Service - May 1977 - M 65-20

-----

Found - Alum. cap on 3/4" Iron rod marked "U.S.P.C. Prop.  
Cor. 1/4 S18 only R.E. 4287"  
60" Fir stump, N.69°E., 29.5 ft.  
60" Fir stump, S.22°E., 37.0 ft.  
10" Hemlock, S.18°E., 11.2 ft. (Orig.)  
New BTs- 8" D.Fir bears East, 131.5 ft.  
8" D.Fir bears S.02°E., 98.0 ft.  
Both trees scribed "W 1/4 S18 BT."