

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 12 Page(s) 4870)

-----  
Set Maple post 3 ft. long, 3" sq., 24" in the ground for ¼  
sec. corner marked on E. and W. faces "¼ S", from which  
A Fir 24" dia., bears N.40°W., 25 lks. dist. mkd. ¼ S BT  
A Maple 8' dia., bears N.80°E., 22 lks. dist. mkd. ¼ S BT

GLO survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4784)

-----  
Set basalt stone 15x14x8 ins., 10" in ground for ¼ sec. cor.  
marked ¼ on W. face, from which  
A Pine 24" dia., bears S.18°E., 65 lks. dist. mkd. ¼ S7 BT  
A Pine 24" dia., bears N.31°W., 84 lks. dist. mkd. ¼ S12  
BT.  
From this cor., the old cor. bears N.9°29'W., 6.43 chs. dist.  
I destroy the old cor.

GLO survey by Charles E. Roberts, U.S. Deputy Surveyor, under  
Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12  
Page(s) 4884½)

-----  
Intersect ¼ sec. cor. to sec. 7, T27S R1W which is a basalt  
stone, 7x7x12 ins. above ground, marked and witnessed as  
described by the surveyor general.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Oct. 1968 - C.S. File 54/40-97

-----  
Found - Corner stone mkd. "X" on top and "¼" on W. face,  
firmly set.  
Orig. 24" now 38" Pine, alive, S.18°E., 42.9 ft.,  
open and find scribe.  
Orig. 24" now 30" Pine stump, N.31°W., 55.4 ft. open  
and find scribe.

Set Brass cap at cor. mkd: County Surveyors Office  
T 27 S  
R2W | ¼ S7 R1W  
1968

Set old corner stone alongside.  
New BTs- 13" W.Fir S.24°E., 12.0 ft. mkd. ¼ S7 CS BT.  
11" W.Fir N.52°E., 16.8 ft. mkd. ¼ S7 CS BT.

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Romanso E. Ware - For: U.S. Forest Service - July  
1980 - M 79-50

-----  
Found - 1968 DCSO brass cap.  
12" Fir, N.52°E., 16.8 ft., scar.  
16" Fir, S.24°E., 12.0 ft., scar.  
24" Fir, S.18°E., 42.9 ft., visible scribes.  
Set post and sign 5.0 ft. North.