

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION CC for Secs. 6 & 7 only, (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 12 Page(s) 4853-54)

-----  
(9.30 chs. S. of the cor. of secs. 1, 6, 7 and 12)  
Set a basalt stone 15x8x8 ins., 10" in ground for closing corner for secs. 6 and 7, marked CC on E. and 5 notches on S. and 1 on N. edges, from which  
A Maple 8" dia., bears N.52°E., 40 lks. dist. mkd. T27S R1W S6 BT.  
A Fir 16" dia., bears S.11°E., 45 lks. dist. mkd. T27S R1W S7 BT.

Fd. and used in GL0 survey by Charles E. Roberts, U.S. Deputy Surveyor, under Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4884½)

Survey by Burton W. Holt - Wit: Jim Coon - Dec. 3, 1960 - C.S. File 51/100-3

-----  
CC as determined by original BT:  
Found - 12" D.Fir S.12°E., 29.7 ft. in good condition with scribing visible.  
The 7" Maple N.52°E., 26.4 ft. was removed in road construction.  
Found 8" x 10" x 12" Stone at corner.  
Set 1" x 36" Iron pipe with brass cap at corner marked:  
T27S  
R | S 6 R  
2 | S 7 1  
W LS 418 W  
1960  
Rescribed OBT above old scribes marked CC S7 BT.  
New BT - 18" D.Fir N.84°E., 100.2 ft. to face of tree, mkd. CC S6 T27S R1W BT.  
USFS road passes between NE. BT and corner.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel; M. Stone, crew - Dec. 1963 - C.S. File 49/28-16

-----  
Found - Brass cap set in 1960. Also orig. rock alongside. 18" D.Fir N.84°E., 100.2 ft. (to face) bark scribing visible. This tree is across road from corner. Tree alive and in good condition.  
D.Fir, S.12°E., 29.7 ft., bark scribing visible. This tree is still alive but in poor condition.  
New BT- 20" D.Fir S.30°E., 40.8 ft. "T27S R1W CC S7 CS BT

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION CC for Secs. 6 & 7 only, (West)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Survey by Loyd R. Moffitt LS #944 - For: U.S. Forest Service  
June 1986 - C.S. File 62/30-27

-----  
Found - A 2½" brass cap on a 1" Iron pipe.  
          19" Fir, bears S.30°E., 40.8 ft. scar visible.  
          23" Fir, bears S.12°E., 29.7 ft., bark scribe vis.  
New BT - I marked a 12" Fir BT which bears N.64½°E., 111.0  
          ft. from the corner, scribed "T27S R1W S6 CC BT".  
          Nailed LS 955 brass washer to BT scribe.