

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100609

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T27-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by S.C. Flint, Contract #459, dated August 3, 1882
- (DCSO records Vol. 12 Page(s) 4869-70)

Set Laurel post 4 ft. long, 4" sq., 24" in the ground, for corner to secs. 1, 12, 6 and 7, marked T27S S6 on NE.; R1W S7 on SE.; R2W S12 on SW.; and S1 on NW. faces, with 1 notch on N. and 5 notches on S. edges, from which
A Fir 38" dia., bears N.65°E., 70 lks. dist. mkd. T27S R1W S6 BT.
A Fir 10" dia., bears S.50°E., 17 lks. dist. mkd. T27S R1W S7 BT.
A Fir 20" dia., bears S.45°W., 33 lks. dist. mkd. T27S R2W S12 BT.
A Fir 30" dia., bears N.80°W., 20 lks. dist. mkd. T27S R2W S1 BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 12 Page(s) 4854)

I destroy all marks on old corner referring to secs. 6 and 7.

GL0 survey by Charles E. Roberts, U.S. Deputy Surveyor, under Contract #759, dated Oct. 26, 1904 - (DCSO records Vol. 12 Page(s) 4885)

The cor. of secs. 1 and 12 on the range line which is a basalt stone firmly set 5x6x8 ins. above ground, marked and witnessed as described by the surveyor general.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Aug. 18, 1962 - C.S. File 51/163-11

Found - 5"x6"x8" stone, 5 notches on S. side.
28" W.Fir S.50°E., 17 lks. (wood scribe visible)
30" Fir N.73°W., (Rec. N.80°W.) 20 lks. (faint bark scribe)
34" Fir S.52°W., (Rec. S.45°W., 33 lks. (bark scribe destroyed)
Set 3/4" x 30" Iron pipe.
Scribed- 10" Fir, N.31°W., 22.4 ft.
34" Fir, S.52°W., 23.8 ft.

Fd. OK, Oct. 24, 1968, V.Tracy - DCSO - C.S. File 54/40-98

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 100609

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T27-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BHW Engineering - Romanso E. Ware - For: U.S. Forest Service
March 1977 - M 65-13

Found - 3/4" Iron pipe.
30" Hemlock snag, S.50°E., 11.2 ft., scribing vis.
30" D.Fir snag, S.52°W., 23.8 ft. scribing visible
12" Fir, N.31°W., 22.4 ft., good face.
42" D.Fir, N.73°W., 13.2 ft., no scar or scribe vis.
New BT - 16" D.Fir bears S.30°W., 104.5 ft. scribed "T27S R2W
S12 BT". Washer set in face.

Survey by Dennis Gaylord, U.S. Forest Service (Deputized by
the DCS) Wit: Travis Worthen - July 7, 1977 - C.s. File
59/38-5

Found - 3/4" Iron rod set by Johnstone in 1962, with corner
stone lying alongside. Corner stone has five
notches on one edge.
31" W.Fir snag, bears S.50°E., 11.5 ft. scribing
visible on previously opened blaze.
11" D.Fir, bears N.31°W., 22.2 ft. has healed scars.
37" D.Fir, bears N.71°W., 14.5 ft., no scar or
scribing visible.
33" D.Fir snag, bears S.52°W., 23.8 ft. has a healed
scar.
17" D.Fir, bears S.28°W., 104.2 ft. (Rec. S.30°W.,
104.5 ft.) scribing visible "T27S R2W S12 BT" on
a double blaze. Lower blaze has an alum. washer
set in face mkd. "LS 1005"

(All measurements to center of BTs)

Removed 3/4" Iron pipe and in its place I SET a 2½" brass cap
on a 1" iron pipe stamped: County Surveyors Office

T27S R2W
S 1 | S6
S 12 |
1977

No new accessories. I placed County BT signs on all BTs.
Corner lies 75 ft. East of F.S. Road #2612D.