

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4844)

-----  
Set a basalt stone 15x10x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which  
A fir, 24" dia., bears North, 13 lks., mkd: ¼ S30 BT.  
A fir, 24" dia., bears S.63°W., 29 lks., mkd: ¼ S31 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-62

-----  
Found - 24" D.Fir, now stump, North 7.9 ft., shows good scar.  
24" D.Fir, now stump, S.63°W. 19.1 ft., opened for scribe S31  
Set - Brass Cap at ¼ cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE ¼ S 30  
1969 S 31  
New BTs- 17" D.Fir S.21½°W. 34.3 ft. mkd: ¼ S31 CS BT.  
36" D.Fir N.63½°E. 75.3 ft. mkd: ¼ S30 CS BT.