



TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

John Ransom, USFS - Jonathan Drew - 1/2011 - CS File 65/72-15  
-----

Found - 1" Iron Pipe with 2½" County Surveyors Office Brass  
Cap Projecting 14" above mound of stone, cap  
marked "T27S R1W S19 ¼ S30 1969" "County Surveyors  
Office"

30" Cedar Snag N.17°E., 49.0 ft. Scribing Visb. on  
part. healed double Blz

Root hole S.48°E., 22.3 ft. Rotted remains Cedar  
found down the hill

32" fir stump S.32°E., 56 ft. Scribing Visb. on  
part. healed double blz.

21" Cedar Stump S.30°W., 41.6 ft. "¼S30BT" Visb. on  
open double blaze.

New - Painted BTs red with 6" wide band at head height,  
painted face blaze, new nails on tags. Added 2  
new trees:

7" Fir Bears N.19°18'E., 10.43 ft. scribed "¼S19"  
"Bt" on double blaze 10.14' to washer

7" Fir Bears S.54°33'E., 13.75 ft. Scribed "¼S30"  
"BT" on Double Blaze 13.4' to washer.

All new trees include a ¾" brass washer nailed  
between B and T on lower blaze, Washer stamped  
"LS2561"

Note - Corner is on west slope in timber approx. 500' above  
white creek. Take 2792 road to 150 spur heading  
west, follow to end and continue west to small  
draw, follow draw NW to corner ~500' from creek

PLANE COORDINATE POSITION DATA

State OR Zone UTM-10M

North 4782826

East 511012.4

Estab. By GCDB