

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION W C 1/4 Cor Secs 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747 dated May 5, 1902 - (DCSO recs Vol 11 Pg) 4851

Set a basalt stone 12x8x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
 A fir, 24" dia., bears N.60°E., 29 lks., mkd: ¼ S7 BT.
 A fir, 24" dia., bears S.15°E., 19 lks., mkd: ¼ S18 BT.

Burton W. Holt, #418 - March 13, 1963 - C.S. File 51/100-4

Found - Both orig. BTs & the stone mkd: ¼. Removed the stone because of road construction through the corner., The BT in Sec. 7 was removed due to const. but BT in Sec. 18 still remains.
Set - 1"x36" IP w/brass cap 18 ft. south of the true corner for a witness corner. mkd cap:
 T27S R1W W C ¼ S 7 COR. IS 18' NORTH
 1963 S 18 L S 418
New BTs- 40" D.Fir bears S.12°W., 9.1 ft mkd: ¼ S18 BT (bark scribed)
 22" D.Fir bears N.55°E., 99.8 ft. mkd: ¼ S7 BT (This BT lies north of road)
The true ¼ corner lies on the cut bank of the Shadow Sale Road & the witness corner is above the cut bank. Placed orig. stone beside the brass cap, which is approx. 32 ft. S of road center.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969- C.S. File 54/94

Reported found

Romanso Ware & Ronald Quimby - For: USFS - July 1980 - M79-50

Found - 1963 county brass cap mkd: T27S LS 418 ¼ S7 S18 R1W WC Cor 18 ft. North
 42" Fir S.14°W., 9.6 ft. vis. scribes.
 24" Fir N.52°E., 99.8 ft. shows scar.
Set - Post & sign 5.0 ft. South.

Michael J. Schwartz - Umpqua National Forest - June 2010 - M161-14A&B

Found - The BC (properly mkd) & IP set by the County Surveyors Office in 1963 for the Witness Corner,
 A 44" Fir, S.14°W., 9.6 ft., healed blaze.
 A 28" Fir, N.52°E., 99.8 ft., healed blaze.