TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4854)

Set a basalt stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 8" dia., bears N.52°E., 16 lks., mkd: ¼ S6 BT.
A cedar, 24" dia., bears S.21°E., 18 lks., mkd: ¼ S7 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-5

Found - Stone set at ¼ cor. mkd: "¼" on the north face.
24" now 34" cedar, S.21°E., 11.2 ft. shows good scar
8" now 22" fir, N.52°E., 10.0 ft. shows good scar.
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS OFFICE 1969 T27S R1W ¼ S 6 / S 7
All BTs Ok & tagged.

Romanso Ware & Ronald Quimby - For: USFS - July 1980 - M79-50

Found - 1969 County brass cap.
22" D.Fir N.55°E., 11.7 ft. good scar.
42" Cedar, S.25°E., 10.7 ft. good scar.
Set - Post & sign 5.0 ft. North.