

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 142700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only, T26-1

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4102)

-----

Set a basalt stone 12x8x8 ins., 8" in the ground for ¼ sec. cor. on S. bdy. of sec. 31, marked ¼ on N. face, from which  
A Cedar 12" dia., bears N.76°E., 73 lks. dist. mkd. ¼ S31 BT.  
A Hemlock 12" dia., bears N.24°W., 45 lks. dist. mkd. ¼ S31 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 17, 1969 - C.S. File 54/94-90

-----

Found - No trace of Corner stone nor NW. BT.  
12" now 25" Cedar, N.76°E., 48.2 ft. scribe visible.  
Set Brass cap at cor. mkd: County Surveyors Office  
T26S R1W ¼ S 31  
T27S

1969

New BT - 10" Hemlock N.77°W., 29.2 ft. mkd. ¼ S31 CS BT.  
Brg. and Dist. btwn ¼ sec. 6 and ¼ sec. 31 is S.82°W., 117.6 ft. (Rec. West, 125.4 ft.)