

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by S.C. Flint, Contract #473, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4767)

-----  
Set post 48x4 ins. firmly in the ground for stand. cor. to  
secs. 31 and 32 marked S C T27S R1W on N., S32 on E. and S31  
on W. faces, with 5 notches on the E. and 1 notch on the W.  
edges, from which

A Fir 14" dia., bears N.18°E., 77 lks. dist. mkd. T27S R1W  
S32 BT.

A Fir 12" dia., bears N.25°W., 63 lks. dist. mkd. T27S R1W  
S31 BT.

A Fir 8" dia., bears S.35°W., 15 lks. dist. mkd. S BT.

GL0 survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4777-78)

-----  
(76.00 chs.)  
Old stan. sec. cor. on line which I destroy.

(80.00 chs.)  
Set a basalt stone 12x8x6 ins., 8" in the ground for stan.  
cor. of secs. 31 and 32, marked S C on N. with 5 grooves on  
E. and 1 groove on W. faces, from which

A Fir 20" dia., bears N.40°E., 32 lks. dist. mkd. T27S R1W  
S32 BT.

A Fir 12" dia., bears N.84°W., 56 lks. dist. mkd. T27S R1W  
S31 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew -  
Nov. 17, 1969 - C.S. File 54/94-46

-----  
Found - 12x8x6 stone, firmly set, mkd. with grooves E & W.  
12" now 26" Fir N.84°W., 37.0 ft. shows good scar.  
20" now 30" Fir, N.40°E., 21.1 ft. shows good scar

Set Brass cap at cor. mkd: County Surveyors Office  
T27S R1W S 31 | S 32  
T28S S 5

1969

Bearing trees OK and tagged.  
Rec. distance between corners 13.2 ft., found to be 15.5 ft.