

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4842)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A hemlock, 24" dia., bears S.29°E., 73 lks., mkd: ¼ S32 BT
- A fir, 60" dia., bears N.60°W., 18 lks., mkd: ¼ S31 BT.

Douglas Co. Surveyors Office - Dennis Gaylord, USFS & DCSO Deputy - Jan. 12, 1978 - C.S. File 59/46-2

Found - A stone set solidly in place marked "¼" on the west face. Stone measures 14x12x6"

- A 60" D.Fir snag bears N.60°W., 10.9 ft. (Rec. 11.9 ft.) Bark shows old axe marks.
- Orig. BT to the SE is down & badly decomposed.
- Placed County BT sign on snag.

Set - Moving orig. stone aside, I Set in it's place a 2½" brass cap on a 1" I.P. Brass cap stamped

County Surveyors Office
T 27 S R 1 W
¼ S 31 | S 32
1978

I buried the corner stone alongside. I built a mound of stones around the brass cap.

New BTs- A 18" D.Fir bears S.7°W., 11.5 ft. scribed "¼ S31 CS BT" on a double blaze.

- A 22" D.Fir bears N.71½°E., 26.2 ft. scribed "¼ S32 CS BT" on a double blaze.

Place County BT signs on both BTs.