

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4842)

Set a basalt stone 24x12x8", 18" in the ground for cor. of secs. 29, 30, 31, & 32 mkd with 1 notch on S & 5 notches on E edges, from which

- A fir, 30" dia. bears N.15°E. 67 lks. mkd: T27S R1W S29 BT
- A fir, 24" dia. bears S.78°E. 93 lks. mkd: T27S R1W S32 BT
- A fir, 8" dia. bears S.40°W., 26 lks. mkd: T27S R1W S31 BT
- A fir, 30" dia. bears N.15°W. 100 lks mkd: T27S R1W S30 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-61

Found - 24x12x8" stone at sec. corner, no marks.
30" D.Fir now snag, N.15°E., 44.2 ft. shows scar.
24" Fir, now stump, S.78°E., 61.4 ft. opened for scribe "27S R1"
8" Fir, now 26" S.40°W., 17.2 ft. shows good scar.
30" Fir, now stump N.15°W., 66.0 ft shows good scar.

Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 30 | S 29
1969 S 31 | S 32

New BTs- 26" hemlock N.89°W., 46.1 ft mkd: T27S R1W S30 CS BT
14" D.Fir N.58°E., 15.7 ft. mkd: T27S R1W S29 CS BT
24" D.Fir S.69°E., 78.5 ft. mkd: T27S R1W S32 CS BT

Ronald A. Quimby, LS 1654 & Romanso E. Ware, LS 1005 - For: USFS - March 1980 - M79-32

Found - 1" Iron pipe with brass cap.
30" D.Fir snag bears N.15°E., 44.2 ft. with visible scribes.
42" D.Fir stump bears S.78°E., 61.4 ft. with visible scribes.
28" D.Fir bears S.69°E., 78.5 ft. with visible face.
26" D.Fir bears S.40°W., 17.2 ft. with visible scribes.
52" D.Fir stump bears N.15°W., 66.0 ft. with good scar.
26" Hemlock bears N.89°W., 46.1 ft. with visible scribes.
24" D.Fir bears N.58°E., 15.7 ft. with good scar.

Set fiberglass post 4.5 ft. south of corner.