TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4844)

Set a basalt stone 15x10x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 20" dia., bears N.21°E., 87 lks., mkd: ¼ S29 BT.
A cedar, 30" dia., bears S.55°W., 29 lks., mkd: ¼ S30 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-91

Found - No trace of corner stone.
30" now 38" Cedar, S.55°W., 19.1 ft. opened for scribing "¼S"
20" now 34" D.Fir, N.21°E., 57.4 ft shows good scar.
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS T27S R1W OFFICE 1969 ¼ S 29|S 30
New BTs- 12" Hemlock S.79°E., 18.6 ft. mkd: ¼ S29 CS BT
8" Hemlock S.81°W., 6.2 ft. mkd: ¼ S30 CS BT

Ronald A. Quimby, LS 1654 & Romanso E. Ware, LS 1005 - For: USFS - March 1980 - M79-32

Found - Douglas County Surveyors brass cap on 1" iron pipe.
40" Cedar bears S.55°W., 19.1 ft with visible scribe
36" D.Fir bears N.21°E., 57.4 ft. with good scar.
14" Hemlock bears S.79°E., 18.6 ft with visible scribe.
10" Hemlock bears S.81°W. 6.2 ft with visible scribe
Note - Set fiberglass post with sign 54-4 4.0 ft. north of corner.